

Software Name: AWK-5222 MIB File

Version No.	Build Code	Supported OS	Apply to (full model name)	New Feature(s)	Change(s)	Enhancement(s)	Bug(s) Fixed	Additional Note(s)
1.9	14120413	N/A	AWK-5222-US, AWK-5222-EU AWK-5222-US-T, AWK-5222-EU-T AWK-5222-M12-US, AWK-5222-M12-EU AWK-5222-M12-US-T, AWK-5222-M12-EU-T	N/A	N/A	N/A	N/A	ETSI EN 300 328 Certification Update from v1.7.1 to v1.8.1
1.8	14092614	N/A	AWK-5222-US, AWK-5222-EU AWK-5222-US-T, AWK-5222-EU-T AWK-5222-M12-US, AWK-5222-M12-EU AWK-5222-M12-US-T, AWK-5222-M12-EU-T	<ol style="list-style-type: none"> 1. Add wirelessSniffer mode to overviewOperationMode. 2. Add vapEAPanonymous and vapEapUser to vapTable table. 3. Add Turbo Roaming settings to turboRoamingTable. 4. Add systemLogRssiReport. 5. Add snmpRo_community and snmpRw_community. 6. Add emailSntpUserName. 7. Add wlanClientMAC, wlanClientConnectionTime, wlanClientRSSI, wlanClientTotalTx, wlanClientTotalRx, wlanClientLastTotalTxRxResetDate, wlanClientAPMAC, wlanClientAPVlanID index to wlanClientListTable. 8. Add wirelessStatusNumericalIndexTable. 9. Add dhcpClientNumericalListTable. 10. Add miscWebIdleTimeLogoutMins. 	<ol style="list-style-type: none"> 1. Change dhcpServerLeaseTime to dhcpServerLeaseTimeMinute. 2. Change index of relayStatusAckTable from relayType to relayIndex. 	N/A	N/A	N/A
1.7	11102114	N/A	AWK-5222-US, AWK-5222-EU AWK-5222-US-T, AWK-5222-EU-T AWK-5222-M12-US, AWK-5222-M12-EU AWK-5222-M12-US-T, AWK-5222-M12-EU-T	1. No Change	N/A	N/A	N/A	N/A
1.6	11071214	N/A	AWK-5222-US, AWK-5222-EU AWK-5222-US-T, AWK-5222-EU-T AWK-5222-M12-US, AWK-5222-M12-EU AWK-5222-M12-US-T, AWK-5222-M12-EU-T	1. No Change	N/A	N/A	N/A	N/A

Software Name: AWK-5222 MIB File

Version No.	Build Code	Supported OS	Apply to (full model name)	New Feature(s)	Change(s)	Enhancement(s)	Bug(s) Fixed	Additional Note(s)
1.5	10090618	N/A	AWK-5222-US, AWK-5222-EU AWK-5222-US-T, AWK-5222-EU-T AWK-5222-M12-US, AWK-5222-M12-EU AWK-5222-M12-US-T, AWK-5222-M12-EU-T	1. Add snmpRmtMngtEnable node.	N/A	N/A	N/A	N/A
1.4	10080518	N/A	AWK-5222-US, AWK-5222-EU AWK-5222-US-T, AWK-5222-EU-T AWK-5222-M12-US, AWK-5222-M12-EU AWK-5222-M12-US-T, AWK-5222-M12-EU-T	1. Add linkFaultPassThrough.	1. Change index of wlanClientListTable from wlanClientIndex to wlanClientMAC. 2. Change index of dhcpClientListTable from dhcpClientIndex to dhcpClientMAC. 3. Change index of wirelessStatusTable from wlanSsidIndex to wlanVapIndex. 4. Change objects for clientJoined trap from wlanClientIndex to wlanClientMAC. 5. Change objects for clientLeft trap from wlanClientIndex to wlanClientMAC.	N/A	N/A	N/A
1.3	10020800	N/A	AWK-5222-US, AWK-5222-EU AWK-5222-US-T, AWK-5222-EU-T AWK-5222-M12-US, AWK-5222-M12-EU AWK-5222-M12-US-T, AWK-5222-M12-EU-T	1. Add devWMMenable. 2. Add turboRoamingApAliveCheckEnable. 3. Add VLAN group. 4. Add configChange, clientJoined, clientLeft SNMP traps.	1. Add group name to beginning of nodes for each group. 2. Remove wlanDevWifiWlanChannelList. 3. Remove key settings. 4. Remove community nodes. 5. Remove username and password nodes. 6. Add wlanSsidIndex from wlanClientListTable. 7. Add wlanSsidIndex from wirelessStatusTable. 8. Add none(2) to relayAck node. 9. Support read the saveConfig status (success or failure).	N/A	N/A	N/A
1.2	09121101	N/A	AWK-5222-US, AWK-5222-EU AWK-5222-US-T, AWK-5222-EU-T AWK-5222-M12-US, AWK-5222-M12-EU AWK-5222-M12-US-T, AWK-5222-M12-EU-T	No Change	N/A	N/A	N/A	N/A

Software Name: **AWK-5222 MIB File**

Version No.	Build Code	Supported OS	Apply to (full model name)	New Feature(s)	Change(s)	Enhancement(s)	Bug(s) Fixed	Additional Note(s)
1.1	09072302	N/A	AWK-5222-US, AWK-5222-EU AWK-5222-US-T, AWK-5222-EU-T AWK-5222-M12-US, AWK-5222-M12-EU AWK-5222-M12-US-T, AWK-5222-M12-EU-T	1. Add devNoiseProtection.	1. wlanDevWifiWlanTxRange change from 10km to 11km.	N/A	N/A	N/A
1.0	09062313	N/A	AWK-5222-US, AWK-5222-EU AWK-5222-US-T, AWK-5222-EU-T AWK-5222-M12-US, AWK-5222-M12-EU AWK-5222-M12-US-T, AWK-5222-M12-EU-T	First Release	N/A	N/A	N/A	N/A